

## Conseal Acrylic

### Concrete Surface Sealer

#### Description

A clear acrylic sealer designed for applications onto concrete to provide a long lasting dust free sealed surface. This low odour water borne formulation makes Conseal Acrylic the ideal product for use where solvent based products would be undesirable. Suitable for use as a sealer on green and imprinted concrete where its excellent no yellowing and weathering properties are fully utilised.


#### Advantages

- Non flammable, low odour formulation.
- Economical in use and equipment may be cleaned with water.
- Easily applied by low pressure spray, brush or roller.
- Fine particle size ensures excellent penetration

#### Technical Information

Specific Gravity	1.01
Viscosity	20 Cps
Average Particle Size	0.1 µm
Application Temperature	5°C to 35°C
Application Relative Humidity	40% to 90%
Solids Content	20%
Dry Film Thickness	30µm
Re-coating Interval	From previous coat drying up to 2 days
Coverage	6-8m <sup>2</sup> per litre*
Permeability to CO <sub>2</sub>	s <sub>D</sub> <50m
Permeability to Water Vapour	s <sub>D</sub> <50m
Capillary Absorption and Permeability to Water	w<0.1kg/m <sup>2</sup> /h <sup>-0.5</sup>

\*Surface porosity & profile dependent

 0086	
Nufins, Kingston House, 3 Walton Road, Pattinson North, District 15, Washington, Tyne & Wear. NE38 8QA 13 0086-CPD-594215	
EN 1504-2 Surface protection product Coating	
Permeability to water vapour	s <sub>D</sub> <50m
Capillary absorption and permeability to water	w<0.1kg/m <sup>2</sup> /h <sup>-0.5</sup>
Dangerous substances	Comply with 5.3

#### Surface Preparation

The surface to be sealed should be sound and free from all loose materials. Oil and grease must be removed using Desolve. Should the strength or the surface stability of the concrete base be in doubt, we would recommend that a trial patch of Conseal Acrylic be applied to assess its suitability.

#### Application Instructions

Conseal Acrylic should be applied using a low pressure spray, brush or roller as supplied.

Thinning with water should not be necessary. Two coats are normally applied to provide a dust free surface but on very porous concrete a third coat may be necessary. All equipment should be cleaned immediately after use with clean cold water.



## Packaging

Conseal Acrylic is available in 5 and 25 litre polythene bottles.

## Storage

Material should be stored at room temperature, protected from frost and out of the reach of children.

## Health & Safety

Product Safety Data Sheets (SDS) are available from Nufins. SDS sheets are provided to help customers satisfy their safe handling, use and disposal needs as well as assist with any conformance requirements made locally by health and safety regulations.

SDS are continually updated to provide the very latest information to our customers. We therefore recommend contacting our head office to obtain the most recent and accurate SDS before handling and using any product.

## Limitations

Do not use on concrete which is to be submerged in water. Applications should only be made when the temperature is at least 3°C above the dew point. Do not apply at temperatures below 5°C or when rain is expected.

## Technical Support

Through our technical department and laboratories we can offer a comprehensive service to specifiers and contractors. Technical contacts are available to provide further information and arrange demonstrations.

