

Stabilising Primer WB

Acrylic Stabilising Primer

Description

A single component ready to use acrylic primer designed to improve cohesion and surface integrity of a concrete substrate as well as greatly increase the adhesion of any subsequent repair compounds and/or coatings. Economical in use and easy to use. Stabilising Primer is time saving and can improve the finish achieved with many different repair materials and protective coatings.

Advantages

- Long usable life.
- Excellent bond strength to concrete.
- Easy to apply by either brush or roller.

Technical Information

Resin	Acrylic emulsion
Appearance	Milky white liquid
S.G.	1.0
Solids content	24%
Coverage	5 - 8m ² per litre
Bond Strength	>2.0 MPa

Surface Preparation

The substrate must be dry, clean and free of loose material. Brushing the surface or jet washing are preferred methods. If the surface has been contaminated with moss or lichen then the surface should be treated with Nufins *Fungicidal Wash*.

Mixing

Stabilising primer is supplied ready to use.

Application Instructions

The prepared surface should be liberally coated with the stabilising primer either by brush or roller. Repair materials and protective coatings may be applied once the primer has dried.

Clean all equipment immediately after use with cold water.

Packaging

Stabilising Primer is supplied in 5 Litre units.

Storage

Stabilising Primer has a shelf life of 12 months when stored unopened at moderate temperatures. Protect from frost.

Health & Safety

Product Safety Data Sheets (SDS) are available from Nufins. SDS sheets are provided to help customers satisfy their safe handling, use and disposal needs as well as assist with any conformance requirements made locally by health and safety regulations.

SDS are continually updated to provide the latest information to our customers. We therefore recommend contacting our head office to obtain the most recent and accurate SDS before handling and using any product.

Limitations

Material should not be used in conjunction with cementitious materials below 5°C.

Technical Support

Through our technical department and laboratories we can offer a comprehensive service to specifiers and contractors. Technical contacts are available to provide further information and arrange demonstrations.

