

Biolease Standard

Environmentally Friendly Concrete Mould Release Agent

Description

Biolease Standard is a blend of bio-degradable vegetable oils emulsified in water and is designed for use in general site operations and pre-cast yards. The oil forms a physical barrier between the form and the concrete with the surfactant working in conjunction with the alkalinity of the concrete to produce a high standard of finish.

Advantages

- VOC free and low odour
- Non-flammable
- Safe to use and environmentally friendly
- Readily bio-degradable
- Clean equipment with water
- Non-staining, suitable for white or coloured concrete
- Easy to apply by spray or brush
- Not easily washed off by rain
- Forms may be stripped early when concrete permits
- Suitable for the application of other coatings, sealers and mortars

Technical Information

Approved by WRAS for use with potable/wholesome water.

Tested in accordance with BS6920:2000.

Note: Coverage will depend on surface porosity and texture.

Application Instructions

An even thin film of Biolease Standard should be applied by either low pressure spray, brush or an absorbent applicator. Applications should be performed a minimum of 1 hour prior to concrete installation, allowing the evaporation of the water phase, leaving a clear oily film. Over application should always be avoided, particularly on steel moulds as this can potentially pool, trapping the water phase and accelerate rust formation.

Consideration should be given to re-application if the coated formwork if stored for more than 14 days in an exposed environment. On vertical forms excess material accumulating at the bottom of the form should be removed. On untreated timber surfaces additional coats maybe required. Do not use below 5°C.

Packaging

Biolease Standard is available in 25 litre and 210 litre drums and in 1000 litre bulk tanks.

Storage

The shelf life is 6 months when stored unopened in dry, normal conditions and away from direct sunlight. Protect from frost.

Roll or agitate container prior to use and especially important after long storage periods.

Health & Safety

Product Safety Data Sheets (SDS) are available from Nufins. SDS sheets are provided to help customers satisfy their safe handling, use and disposal needs as well as assist with any conformance requirements made locally by health and safety regulations.

SDS are continually updated to provide the very latest information to our customers. We therefore recommend contacting our head office to obtain the most recent and accurate SDS before handling and using any product.



Technical Note

Biolease Standard, when used in accordance with the stated recommendations, does not cause staining. Concrete “staining” can be caused by a number of factors on which our technical department can advise.

Disclaimer

The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied themselves independently as to the suitability of our products for their own particular purpose. In no event shall Nufins be liable for consequential or incidental damages.

Users must always refer to the most recent issue of the Technical Datasheets, copies of which will be supplied on request.

Technical Support

Through our technical department and laboratories we can offer a comprehensive service to specifiers and contractors. Technical contacts are available to provide further information and arrange demonstrations.

